


Verteiler distributor ----- Empfänger receiver	SDH
	SDW
	SCK



Technical drawing of a rectangular plate with the following dimensions and features:

- Overall length: $47,5 \pm 0,1$
- Overall width: $3,75 \pm 0,05$
- Distance from the left edge to the first hole: $2,5 \pm 0,1$
- Distance from the right edge to the last hole: $2,5 \pm 0,1$
- Distance between the first and second holes: $1,9 \pm 0,1$
- Distance between the last two holes: $1 \pm 0,1$
- Two rows of holes, labeled (L) and (M).
- Center-to-center distance between holes in row (L) is ϕ .
- Center-to-center distance between holes in row (M) is ϕ .

-VV-			
Verpackungscode / packing code			
VV	Verpackungsart / packaging		Bemerkung / remark
LO	lose, geschüttet / slack, poured		WN 50.225
EM	Einzelmagazin / single magazine		WN 50.225
-W-			
Kontaktcode / contact code			
W	Kontakt Artikel-Nr contact part no.		Material material
			Veredelung plating
0	L = R 6169.050 M = R 6169.050 (180° gedreht / turned)		CuZn
			Sn
-CCC-			
Material und Farbcode material and colour code			
Materialinformation siehe Kundenzeichnung material data see customer drawing			
Leergehäuse / housing: MHL 7230-...-G			
PA66-GF25			
Code-Nr. / code no.		Farbe / colour	
361		rot / red	
605		moosgrün / moos green	
905		schwarz / black	
960		natur / nature	
Ergänzung am Ende der Artikelbezeichnung: -G appendix at the end of the part description:			
-NN-			
Farbmarkierung colour marking			
Bereich / area "B"			
Code-Nr. für Farbmarkierung siehe WN 30.83 code no. for colour marking see WN 30.83			
00	ohne Farbmarkierung without colour marking		

Fehlende Maße und Hinweise
siehe separate Kundenzeichnung
Missing dimensions and notes
see separate customer drawing

vereinfachte Darstellung
einer möglichen Abart
simplified representation
of possible variation

A diagram of a 4-bit register. It consists of a horizontal rectangle divided into four equal sections. Above each section is a number: 4, 3, 2, and 1 from left to right. Below each number is a vertical line representing an input. Below the rectangle are four small gray squares representing output buffers. An arrow points to the input line for '2', and a triangle with a dot inside is shown above the output buffer for '2'.

Codierung
keying

Freimachung nach letzter Kammer (0,75mm)
cut-out after last chamber (0.75mm)

achten Sie die allgemeinen Sicherheits- und Verarbeitungshinweise für Steckverbinder und Kontakte: http://www.stocko.de/catalog-pdf/sicherheitshinweise.pdf Respect general safety and processing information for connectors and contacts: http://www.stocko.de/catalog-pdf/safety-information.pdf	g	n
---	---	---